

DLL version = 0121 OPS_CCYL (2).txt

File version = 4
OXE version = 0110

Soft Key = 71178fd0b02fed039626


Cpu Id 0 = A0B3CCEC09F0
Cpu Id 1 = A0B3CCEC0A28

Your System CPU-Id:a0b3ccecc09f0
System CPU-Id found


Handle 4760 = A0B3CCEC09F0

Timestamp :
Mon Sep 5 10:56:31 2016

SP OPS_Version = 00000		
1 Group Telephony	=	99999
2 M Phonebook users	=	25/ 25
4 Hotel guest sets	=	0
5 Multilingual voice prompts	=	0
6 Hotel: AHL on V24	=	0
9 PSTN B channel	=	99999
10 Voice Guide	=	1
12 DISA	=	0
13 ECS Engine	=	99999
14 Integrated metering report	=	0
19 Corporate netw. (ABC,ABCVPN,ISVPN)	=	0
20 Automated attendant	=	0
21 Nb of VPS ports	=	0
29 DECT/PWT Engine	=	0
38 Infocenter link	=	0
39 Performance	=	0
40 Real Time Incidents	=	500
41 DECT register	=	500
42 Accounting users	=	500
44 4059 SBC	=	0
45 4059 BLF	=	0
46 Fax server ABC-A link	=	0
47 Alarms	=	500
49 Directory	=	0
50 Configuration	=	500
51 Real Time Metering on V24	=	500
52 4635 Basic Package	=	0
56 4635 Networking OctelNet	=	0
57 4635 Fax manager	=	0
58 4635 Call manager	=	0
59 4635 Hotel manager	=	0
60 4635 Nb of ports	=	0
61 4635 Nb of hours	=	0
62 4635 Nb of languages	=	0
63 4635 Attendant manager	=	0
65 4635 Recording manager	=	0
66 4635 Networking AMIS	=	0
75 Networking hospital	=	1
76 M CCD Agents	=	0
77 CCS mono-site	=	0
78 CRI call record interface	=	0
79 ISVPN	=	0
80 VPN	=	0
81 Meet me conf. between 29 parties	=	0
82 Nb of DECT terminals	=	0
83 Flow Metering on Ethernet	=	500
84 4635 users	=	0
86 Automatic directory pop-up	=	0



87	Beta Test	=		0
89	Notification server	=		0
90	M Roaming DECT/PWT	=	0/	0
91	Voice guide record from Reflexes	=		0
94	WMI workforce manager interface	=		0
97	VPS users	=		0
98	Accounting for local calls	=		0
99	Accounting for ABC calls	=		0
100	CSTA profile	=		0
101	CSTA monitoring requests	=		0
102	CCS multi-site	=		0
103	Real Time Interface	=		0
105	Compressed calls	=		0
106	Transfix Access X24/V36	=	99999	0
107	4635 Visual messenger	=		0
109	4635 IP Octel Networking	=		0
110	4635 Global message redundancy	=		0
111	Ubiquity	=		0
113	CSTA pilots monitoring	=		0
114	TSAPI server	=		0
115	CCA softphone	=		0
116	ECC My Softphone (4980 Std)	=		5000
117	M ECC 4980 Option (4980 Adv)	=	0/	5000
119	4980 nomadic logged	=		5000
121	CLIP on VPS	=		0
122	ACAPI via CMIP	=		500
123	CSTA IVR ports monitored	=		0
125	CCweb Agents	=		0
126	Hotel AHL link	=		0
127	M Encryption DECT/PWT users	=		0
128	4615 ports	=		0
129	M ECC My Softphone (4980 Grp)	=	0/	5000
130	CSTA voice recording type	=		0
131	Remote LIO	=		0
132	IP-Trunk	=		0
133	Mastered conference	=		0
134	Multi-tenant	=		0
135	G729A Server	=		90
136	Priority	=		0
137	Call restriction	=		0
138	IP Clients	=		331
143	TAPI premium server	=		0
145	CSTA Recording B channel	=		0
146	PWT mobility (UTAM)	=		0
148	IP Call Server	=		1
151	4635 VPIM	=		0
152	Ith radio	=		0
153	SNMP Trap	=		1
154	Additional S0 features	=		0
155	Additional safety features	=		0
156	Ith	=		0
157	CCA nomadic	=		0
158	CSTA By-pass	=		1000
160	CCemail Agents	=		0
161	CCoutbound Agents	=		0
162	CCoutpredial Agents	=		0
164	CSTA Record networked	=		0
165	OmniPCX Enterprise release	=		44
166	4980 multi device	=		5000
167	ACR data base read	=		0
168	Nb of HPOV node	=		0
169	Voice detection channels	=		0
173	M Advanced Reflexes users	=	0/	32
174	M Analog users	=	38/	40
175	M Mobile users	=	0/	0
176	M Advanced IP users	=	77/	104
177	M SIP users	=	0/	0
178	4645 Voice mail engine	=		0



	OPS_CCYL (2).txt		
179 M	4645 users	=	0
181	OmniPCX Enterprise	=	1
182	4645 networking	=	0
183	4645 additional language	=	0
184	Integrated Gatekeeper	=	0
185	SIP Gateway	=	1
186	E-CS redundancy	=	1
187	H323 (G711) network link	=	0
188	SIP network links	=	92
189	CCTI agents	=	0
190	RSI call center agents	=	0
191	Campus DECT	=	0
192	DREX Protocol	=	0
193	Embedded voice guides	=	1
194	4645 Portal users	=	0
195	CCD profile	=	0
196	RSI Business agents	=	0
197 M	G729A Client	=	281/ 331
198	G723.1 Client	=	0
199	Version 4400 R5.0 Ux	=	0
200	4400 Mobiles migration	=	0
308 M	Remote extension	=	0/ 0
309	XML telephony	=	5000
310 M	CLIP Z	=	0/ 0
311	ACR Networking	=	0
312	Scripting agents	=	0
313	eCC Gateway	=	0
314	4635 My messaging users	=	0
316 M	Standard Reflexes users	=	0/ 0
317 M	Standard IP users	=	204/ 227
318	XML IPTouch-IP engine	=	0
325	IP-Touch Security Engine	=	0
326 M	Secured IP-Touch Phones	=	0
327 M	IP-Touch Security MCM	=	0
328 M	IP-Softphone Attendants	=	0/ 0
329 M	IP-Softphone Agents	=	0/ 0
330 M	Advanced Mobile IP-Touch Users	=	0/ 0
332 M	PCS max. number	=	0/ 0
335 M	Greeting Assistant	=	0
334	Max. IP recording	=	0
336	IME Stations	=	0
337	SIP External Voice Mails	=	0
342 M	ABC-IP Access Number	=	0/ 0
343 M	MgSec Max Number	=	0/ 0
345 M	SIP extension users	=	0/ 0
348 M	Soft MSM lock	=	0/ 0
358 M	Max number of SIP TLS sets	=	0/ 0
359	Max com simultaneous SIP TLS	=	0
363 M	NOESIP TLS users	=	0/ 0
364	Max Attendants 4059EE	=	0
371	IPDEct Users	=	0
384	OXE Media Servers	=	0
385	VoIP channels on OMS	=	0
386	UC as a Service	=	0
467	ARS	=	500
468	Product Type	=	99999
469	G723.1 Server	=	90
396	IPV6	=	0

